

For Earth, For Life
Kubota

Z

KUBOTA Z-SERIES

Z1-421



The best is exactly good enough

A central feature of Kubota's Z1-421 is the zero-turn principle, which makes these mowers uniquely manoeuvrable. Kubota has equipped these machines with additional features that guarantee their excellent cutting quality and impressive large-area performance.

Seat with high backrest

The spacious upholstered operator's seat with its high backrest keeps you comfortable even during extra-long mowing operations.

Adjustable seating position

The seat rails allow you to move the operator's seat back and forth over a wide range. This ensures that you can find the seating position that offers you maximum comfort.

Easy lifting and cutting height adjustment

The mower deck lifting system is operated by foot control making the operation very easy. Adjusting the cutting height is done via a dial gauge on the control panel.

Roll bar as standard

Total peace of mind: for your safety, the Z1-421 is equipped with a high and stable roll bar.

Easy-action steering levers

The two steering levers give you the smooth, precise control you need for fine lawn trimming and working around trees and flower beds. For even greater ease of use, you can adjust the levers to suit your height.

Handy cup holder

The integrated cup holder means that your drink is always ready to hand.

Generous legroom

The large operator platform has ample legroom. This also makes it easier for you to get on and off the machine.



#Features



One mowing deck for top results

The welded mowing deck with 107 cm working width and 114mm depth produces outstanding cutting quality at a professional level. The result is faster and better mowing.



Optional mulching equipment

The optional mulching equipment transforms the standard mower into a high performance mulching mower that produces the finest mulch and feeds it directly back into the turf.



Ergonomic controls

All levers and switches are clearly arranged for quick, easy and user-friendly access.

Precise cutting height adjustment

The cutting height can be adjusted in precise 6 mm steps by simply turning the control dial.



Powerful engine

You can rely on the Kawasaki V-twin engine for every mowing job. Quiet and fuel-efficient, the engine delivers the power you need to get the job done, every time.



Robust gearbox

The independent hydrostatic transmission (HST) delivers concentrated power and efficient transmission to the wheels.



Simple maintenance

You can easily access the oil dipstick and air filter without removing a cover. As there are no lubrication points, servicing the machine is easy. You will also appreciate the practical cleaning connection. Whenever you want to wash off wet grass, all you have to do is connect the hose.

#Technical data

Model	Z1-421	
Engine		
Type	Petrol, air-cooled V-Twin	
Horsepower (Net)	kW/hp	14,1/19
Total displacement	cm ³	726
Fuel tank capacity	l	12,2
Transmission		
Type	Independent T/M	
Supplier and model	Hydro Gear EZT® (ZT-2200)	
PTO drive system	Belt Drive	
Speed control	2 hand levers with height and angle adjustment	
Parking brake system	Cog Loc/Hand Lever	
Tyre size		
Front	11 x 4 – 5 smooth	
Rear	18 x 7,5 – 10 turf	
Travelling speed range		
Forward	km/h	0 – 10,5
Reverse	km/h	0 – 6,4
Dimensions		
Overall length	mm	1890
Overall width w/o discharge deflector	mm	1075
Overall height	mm	1650
Wheelbase	mm	1235
Weight	kg	282
Mower deck		
Cutting width	cm (inch)	107 (42)
Discharge	Side (Mulching kit available as option)	
Cutting height ranges	mm (inch)	38 – 108 (1,50 – 4,25)
Cutting height increments	mm (inch)	6 (0,25)
Deck pan depth	mm (inch)	114 (4,5)
Deck pan thickness	Ga. (mm)	11(3,0)
Deck construction	Fabricated	
Mower location	Mid mount	
Mounting method	Parallel linkages	
Adjustment of cutting height	Dial adjustment system	
Mower deck lifting method	Mechanical Foot Lift Pedal	
Driving method	Belt Drive	
Number of Blades	2	
Washport	1	
Fuel gauge	Sight Window type	
Seat	18inch Deluxe High Back Seat	
Rops	Standard. ISO21299	
PTO clutch	Electromagnetic	
Cup holder	Standard	
Hour meter	Standard	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment.

Please contact your local Kubota dealer for warranty, safety or product information.

KUBOTA (DEUTSCHLAND) GmbH

Senefelder Straße 3–5, 63110 Rodgau

Telefon: +49 6106 873-0, Telefax: +49 6106 873-199, E-Mail: info@kubota.de

<https://www.kubota-eu.com>

Diese Publikation darf ohne vorherige schriftliche Zustimmung von KUBOTA weder ganz noch teilweise in irgendeiner Form vervielfältigt werden. Sie entspricht dem Stand zum Zeitpunkt der Drucklegung. Der Hersteller behält sich das Recht vor, technische Daten ohne Vorankündigung zu ändern. Einige der in der Publikation gezeigten Teile sind optional und gehören nicht zur Standardausstattung. Informationen zu Garantie und Sicherheit sowie weitere Produktinformationen erhalten Sie über den zuständigen KUBOTA-Vertragshändler.

v_1/2021



Kubota