

Multi-Seeder 1200

The floating twin spike rollers of the Multi-Seeder follow the contours, saturating the surface with small holes. The seed is then accurately distributed onto the surface before an adjustable brush sweeps the seeds into the holes. The rear roller then passes over to cover the seed for germination.



Specifications

| | |
|---|----------------|
| SKU | S0001667 |
| Operation | Tractor pulled |
| Working width (m) | 1.2 |
| Working width (inch) | 47.2 |
| Max. Working depth (mm) | 5 - 20 |
| Max. Working depth (inch) | 0.2 - 0.8 |
| Max. Working speed (km h) | 12 |
| Max. Working speed (mph) | 7.5 |
| Weight (kg) | 619 |
| Weight (lbs) | 1365 |
| Hopper capacity (L) | 150 |
| Hopper capacity (cu.ft.) | 5.3 |
| Min. Tractor HP required | 25 |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg) | 910 |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 2006 |
| Min. Pressure (bar) | 1 - 2 |
| Min. Pressure (psi) | 14.5 - 29 |
| Three-point hitch | CAT 1-2 |
| Dimensions (width mm) | 1513 |
| Dimensions (height mm) | 935 |
| Dimensions (length mm) | 1323 |
| Dimensions (width inch) | 59.6 |
| Dimensions (height inch) | 36.8 |
| Dimensions (length inch) | 52.1 |
| Number of rakes | 910 |