

Verti-Drain® 7416

The Verti-Drain® 7416 one of the most versatile aerators in the Redexim range. Capable of working to a depth of 14"/35 cm, the 7416 is well suited to work on sport fields, golf course and other fine turf areas. The tough chassis makes it the ideal Verti-Drain for a range of aeration tasks



Specifications

| | |
|---|-----------------|
| SKU | S0001504 |
| Operation | Tractor Mounted |
| Working width (m) | 1.6 |
| Working width (inch) | 63 |
| Max. Working depth (mm) | 350 |
| Max. Working depth (inch) | 14 |
| Working speed at hole spacing 65 mm (km h) | 0.85 |
| Working speed at hole spacing 2 1 2 inch (mph) | 0.55 |
| Weight (kg) | 870 |
| Weight (lbs) | 1914 |
| Hole distance with 12 mm tines (mm) | 65 |
| Hole distance with 1 2 x 6 inch tines (inch) | 2.5 |
| Hole distance with 18 mm tines (mm) | 130 |
| Hole distance with 3 4 x 9 inch tines (inch) | 5 |
| Hole spacing distance driving direction (mm) | 25 - 195 |
| Hole spacing distance driving direction (inch) | 1 - 7-1/2 |
| Max. Diameter solid tine (mm) | 24 x 350 |
| Max. Diameter solid tine (inch) | 1 x 14 |
| Max. Diameter hollow tine (mm) | 32 x 300 |
| Max. Diameter hollow tine (inch) | 1-1/4 x 12 |
| Min. Tractor HP required | 35 |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg) | 1050 |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 2310 |
| Max. capacity with spacing 65 mm (m ² hr) | 1360 |
| Max. capacity with spacing 2 1 2 inch (ft ² hr) | 12300 |
| Three-point hitch | 3-point CAT 1 |
| Rpm Max. | 500 |
| Gear case oil | 80W90 - 5 |
| Lubricant | EP 2 |
| Slip clutch setting | 800 Nm |