

COMPACT IMPLEMENT RANGE



Implements
engineered
to make your
day easier.





Kubota implements are built to the same high standards as the Kubota machines that use them. From working the land to grass cutting, loading or transporting, Kubota offers a range of compact implement options engineered for quality, durability and performance.

P04. ECONOMY RANGE

P05. CULTIVATION

P06. GRASS MAINTENANCE

P10. ESTATE MAINTENANCE

P12. WINTER MAINTENANCE

P13. TRAILERS AND TRANSPORT

P15. COUNTERBALANCE WEIGHTS

All prices are recommended retail prices in GBP as of March 2025, and are subject to value added tax. Subject to changes in price and product features. The general terms and conditions of KUBOTA UK apply. The publication of this price list renders all previous price lists invalid.

Economy range

Robust, quality implements at the best value.



FLAIL MOWER

Flail Mower W24TS00992
£1,533.00

Flail Mower W24TS00993
£1,600.00

Specifications	W24TS00992	W24TS00993
Use	Paddocks, rough grass/semi-lawn	
Mounting	3 point linkage	
Working width (m)	1.25	1.45
Total width (m)	1.40	1.60
Weight (kg)	160	190
Tractor HP	18-30	20-40
No. of flails (opt)	40	48
No. of hammers	20	24
Cutting height (mm)	25-150	25-150
Side skids + rear roller	Yes	



TOPPER MOWER

Topper Mower W24TS00986
£1,350.00

Specifications	
Width (m)	1.25
Headstock floating	Floating
Offset facility	Yes - 250mm
Depth wheel	Rear adjustable
Cut height (mm)	25 - 150



1-TONNE TIPPING TRAILER

EK Trailer W24TS00987
£1,900.00

Specifications	
Dimensions (mm)	180 x 120 x 34
Sides	Fixed high sides
Tail door	Removable
Tyres	Turf
Tipping	Hydraulic



TRANSPORT BOX

TB1 W24TS00988
£495.00*

Specifications	
Dimensions (mm)	120 x 70
Sides	Removable
Weight capacity (kg)	400

*Note minimum order quantity of 2.



SNOW PLOUGH

Snow Plough W24TS00989
£2,350.00

Specifications	
Width (m)	1.35
Angling	Manual both ways
Rubber wear strip	Replaceable

Cultivation

Heavy-duty performance for efficient soil cultivation.

ROTARY TILLERS

SA105 W20TS01334	SA125 W20TS01335	ZLL140 W30TS00076
£1,997.00	£2,053.00	£2,722.00

Specifications	SA105	SA125	ZLL140
Working width (m)	1.05	1.25	1.40
Max. working depth (cm)	15		18
Weight (kg)	118	130	166
Total width (m)	1.12	1.32	1.53
PTO (rpm)	540		
Tiller (rpm)	253		240
No. of blades	20	24	24-36
Blades per flange	4		4/6
Hitch cat.	1		
Side shift (cm)	34	44	N/A
Side drive	Chain in oil bath		



3-point linkage mounted, PTO driven rotary tillers for cultivating. The depth of cultivation is controlled by the tractor operator on the hydraulic system and adjustable skids to ensure an even depth across the whole work area.

FLAT BALLAST ROLLERS

FR114 W24TS00698	FR214 W24TS00699	FR314 W24TS00883
£1,183.00	£1,334.00	£1,517.00

Specifications	FR114	FR214	FR314
Mounting	Trailed (draw bar type)		
Diameter (mm)	508		
Total width (m)	1.2	1.5	1.8
Weight empty (kg)	180	200	220
Weight with ballast (kg)	360	400	520



3-point linkage mounted flat ballast rollers designed to level and smooth out the surface of uneven ground.

SINGLE FURROW PLOUGH

CP1 W24TS00327
£1,895.00

Specifications	CP1
Mounting	3-point linkage mounted
Reversible	No
Turnover mechanism	N/A
Hitch cat.	1
Working depth (mm)	250
Furrow widths (mm)	254
Weight (kg)	80
Disc couler	Standard
Depth wheel	Standard



3-point linkage mounted ploughs turn the soil over from varying depths, to relieve compaction and bring nutrients to the upper surface, whilst burying unwanted material. Simple, effective, robust and reliable.

Grass Maintenance

Outstanding cutting performance for green spaces, orchards, and paddocks.

REAR MOUNTED ROTARY CUTTERS

GA 1000 W20TS01941

£1,087.00

GA 1200 W20TS01942

£1,230.00

GA 1450 W20TS01943

£1,748.00

Specifications	GA 1000	GA 1200	GA 1450
Mounting at		Rear	
Grass discharge		Rear	
Working width (m)	1.00	1.20	1.40
Weight (kg)	130	146	200
No. of blades		2	
Cutting height (mm)		30 - 100	
PTO speed		540	
Hitch cat.		1	
Blade (rpm)	1350	1042	1028
Blade rotation		Anti-clockwise	



3-point linkage mounted, PTO driven rotary topper mowers for heavy duty paddock maintenance.



Grass Maintenance

REAR MOUNTED FLAIL MOWER

FROG 1120 W20TS01201
£1,696.00

FOX 1200 W20TS01205
£2,559.00

FOX 1400 W20TS01206
£2,611.00

FOX-S 1600 W20TS01210
£3,417.00

Specifications	FROG 1120	FOX 1200	FOX 1400	FOX-S 1600
Use	Light, for a private user	Heavier, with more flails. For heavier use than FROG		FOX with hydraulic side offset - 20 cm
Mounting at	Rear			
Hitch cat.	1			
Working width (m)	1.12	1.20	1.40	1.60
Total width (m)	1.26	1.50	1.60	1.80
Weight (kg)	100	162	175	210
Tractor HP	18	20 - 30		25 - 30
PTO (rpm)	540			
No. of Y flails	56	80	88	100
No. of hammers	28	40	44	50
Cutting height (mm)	30 - 80			
Height regulation	Roller position			
Verticut	-	Y		
Side offset	N/A			Hydraulic - 20 cm



3-point linkage flail mowers for 18–30 hp tractors deliver heavy-duty grass, nettle, and weed cutting with high-performance flails and an even rear discharge.

VERGE MOWERS

VM120 W24TS00885
£8,492.00

VM140 W24TS00886
£9,099.00

Specifications	VM120	VM140
Mounting	Rear	
Hitch cat.		
Working width (m)	1.20	1.40
Total width (m)	1320	1520
Weight (kg)	270	300
Tractor HP	20	30
PTO (rpm)	540	
No. of Y flails	40	48
No. of hammers	20	24
Cutting height (mm)	40	
In Line mowing	90 degree hedge cutting, 65 degree ditch mowing	
Side offset	Y	



3-point linkage, PTO-driven side offset flail mower with 65° ditch and 90° hedge cutting angles for versatile verge maintenance.

Grass Maintenance

ROLLER MOWERS

RM1 W24TS00492
£6,672.00

RM2 W24TS00341
£7,583.00

RM3 W24TS00361
£9,099.00

Specifications	RM1	RM2	RM3
Mounting at		Rear	
Hitch cat.		1	
Working width (m)	1.22	1.82 (71')	2.44 (96')
Total width (m)	1.55 (61')	2.00 (79')	2.65 (104')
Weight (kg)	280	450	620
PTO (rpm)		540	
No. of rotors		2	
Cutting height (mm)		25-100 (1'-4')	
Side offset		N	

3-point linkage mounted PTO driven roller mowers offering the same high-quality finish as a finishing mower but with a striped effect.



CHAIN HARROWS

TH114 W24TS00700
£455.00

TH214 W24TS00684
£682.00

MH114 W24TS00685
£1,107.00

MH214 W24TS00701
£1,258.00

MH1 W24TS00312
£2,093.00

MH2 W24TS00345
£3,336.00

Specifications	TH114	TH214	MH114	MH214	MH1	MH2
Use	General purpose			Heavy grassland		
Mounting	Trailed on pole			Mounted on frame		
Hitch cat.	1					
Total width (m)	1.2	1.8	1.2	1.8	1.98	3
Weight (kg)	50	70	120	160	180	340

Trailed and mounted chain harrows clear debris and moss to promote new growth and prepare fine seed beds.



Grass Maintenance

MULTI-FUNCTION TURF CARE SYSTEM

W24TS00991

£4,300.00

Specifications

Mounting	3-point linkage mounted
Hitch cat.	1
Total width (m)	1.8
Working width (m)	XX
Weight (kg)	200

This versatile 3-point linkage mounted, multi-function system can perform up to four essential turf care tasks in a single pass—surface aeration, de-thatching, rolling, and brushing. By combining these processes, it saves time and effort while promoting healthier, stronger turf growth and delivering a consistently professional finish.



Estate Maintenance

Time saving, easy-to-use equipment for routine maintenance.

POST HOLE BORER

PB1 W24TS00285

£2,350.00

6" Auger W24TS00286

£632.00

12" Auger W24TS00287

£703.00

Specifications	PB1
Mounting	3-point linkage mounted
Boring depth (m)	1
Weight (kg)	100
Augers	6" (150mm) / 12" (300mm)
PTO (rpm)	540

3-point linkage, PTO-driven augers quickly bore clean, vertical holes for secure post placement.



PALLET LIFTER

PT1 W24TS00296

£541.00

PT2 W24TS00343

£668.00

Specifications	PT1	PT2
Mounting	3-point linkage mounted	
Width (mm)	710 (28")	864 (34")
Weight (kg)	40	75
Max lifting weight (kg)	500	1000
Tine length (mm)	900 (36")	1070 (42")

Rear 3-point linkage mounted pallet lifter designed to transport pallets in and around the yard or polytunnel.



Estate Maintenance



MOUNTED SWEEPER

SW2 W24TS00046
£3,971.00

Specifications	SW2
Mounting	Front linkage
Working width (mm)	1575 (69")
Total width (mm)	1750 (62")
Weight (kg)	160
Brushes	Replaceable polypropylene
Height adjustment	By multi-position legs
PTO (rpm)	540

3-point linkage mounted sweeper collectors sweep and collect grass and leaves in large areas with an adjustable brush height.



SWEEPER COLLECTOR

TSC 120 W24TS00293
£8,645.00

TSC 180 W24TS00294
£11,525.00

Specifications	TSC 120	TSC 180
Mounting	linkage arms only	
Working width (m)	1.2	1.8
Total width (m)	1.45	2.05
Weight (kg)	395	560
Tip height (m)	1.2	
Hopper capacity (m³)	1.35	2
PTO (rpm)	540	

3-point linkage mounted, PTO driven sweepers that rotate a full width cylindrical brush.

FERTILISER SPREADER

XL 300 W24TS00303
£1,767.00

XL 500 W24TS00298
£2,047.00

Specifications	XL 300	XL 500
Mounting	3- point linkage mounted	
Hitch cat.	1	
Weight (kg)	60	
Max. laden weight (kg)	400	600
Overall width (mm)	1090	1180
Capacity (L)	300	450
Spread distance (m)	6-18	
PTO (rpm)	540	



FERTILISER SPREADER OPTIONS

XL 300/500 AGITATOR W24TS00307
£213.00

XL 300/500 BOUT LIMITER W24TS00319
£273.00

XL 300 PVC HOPPER COVER W24TS00320
£190.00

XL 500 PVC HOPPER COVER W24TS00315
£190.00

Winter Maintenance

Winter equipment for safer, roads and large areas.

SNOW BLADES TO FIT F90

SB1-F80 W24TS00598

£1,820.00

SB2-F80 W24TS00599

£2,047.00

Specifications	SB1-F80	SB2-F80
Mounting		Front
Hitch cat.		NA
Weight (kg)	220	260
Working width (mm)		1350
Angling		Manual Opt. Hydraulic
Lift		Hydraulic

Robust front-mounted snow blades with hydraulic lift and adjustable angling for fast, reliable snow clearing.



Trailers and Transport

Built to make hauling easy.

TRAILERS

GT 1 C/W G17/G1900 HITCH
W24TS00362
£2,245.00

GT 1 C/W G2160 HITCH
W24TS00382
£2,103.00

GT 2 750KGS
W24TS00354
£2,200.00

TT 1 1.25T TIPPING
W24TS00322
£3,054.00

TT 1B 1.25T TIPPING - BRAKED
W24TS00364
£3,552.00

TT 1BX 1.25T TIPPING (BX)
W24TS00346
£3,054.00

TT 2 2.00T TIPPING
W24TS00339
£3,836.00

TT 2B 2.00T TIPPING - BRAKED
W24TS00365
£4,263.00

TT 3 3.50T TIPPING TRAILER
W24TS00363
£5,763.00

TT 1BX 1.25T TIPPING (BX)
W24TS00882
£6,369.00

Specifications	GT 1		GT 2	TT 1			TT 2		TT 3	
	G17/G1900	G2160	2160	TT 1	TT 1B	TT 1BX	TT 2	TT 2B	TT 3	TT 3B
Body length (mm)	1520		1520	1830			2450		3050	
Body width (mm)	920		920	1220			1540		1830	
Total length (mm)	2300		2300	2450			3300		4300	
Weight (kg)	160		160	250			410		740	
Capacity (kg)	500		750	1250			2000		3500	
Hydraulic tipping	Option		Hydraulic	Hydraulic			Hydraulic		Hydraulic	
Removable corner posts	Std.		Std.	Std.			Std.		Std.	
Removable hinged sides	Std. 300mm		Std. 300mm	Std. 355mm			Std. 355mm		Std. 460mm	
Wheels	18 x 8.50-8		19 x 8.50-8	23 x 8.50-12			23 x 8.50-12		10 x 75-15	
Mesh sides	Opt.- 355mm		Opt.- 355mm 4	Opt.- 450mm			Opt.- 450mm		Opt.- 610mm	
Parking brake	N/A		N/A	Option			Option		Option	
Road light kit	N/A		N/A	Option			Option		Option	
Overrun brake	N/A		N/A	N/A			N/A		Std.	

From 0.5-3.5 tonnes payload capacity, these trailers deliver durable, high-performance hauling that saves time and effort on every job.

OPTIONS

GT 1 HYDRAULIC TIPPING KIT
W24TS00355
£1,213.00

GT 2 HYDRAULIC TIPPING KIT
W24TS00369
£497.00

GT 1 / GT 2 EXTENSION SIDES
W24TS00356
£852.00

TT 1 / TT1B EXTENSION SIDES
W24TS00323
£923.00

TT 1 / TT 1B LIGHTING KIT
W24TS00344
£313.00

TT 2 / TT 2B MESH EXTENSION SIDES
W24TS00350
£1,037.00

TT 2 / TT 2B LIGHTING KIT
W24TS00366
£313.00

TT 3 EXTENSION SIDES
W24TS00741
£1,517.00



Trailers and Transport

QUAD/RTV TRAILERS

RT 1 W24TS00637

£1,066.00

RT 2 W24TS00638 (tailgate doubles as ramp)

£1,421.00

Specifications	RT 1	RT 2
Body length (mm)	1520	1790
Body width (mm)	920	860
Total length (mm)	2300	2570
Weight (kg)	100	160
Capacity (kg)	500	750
Hydraulic tipping	Option	
Removable hinged sides	Fixed 300mm	
Wheels	16 x 6.50-8	17 x 6.50-8
Mesh sides	Opt.- 300mm	

Purpose-built compact trailers, designed for use with the Kubota RTV.



OPTIONS

RT 2 EXTENSION SIDES FOR RT2

W24TS00640

£249.00

TIPPING TRANSPORT BOX

TB114 W24TS00702

£852.00

TB214 W24TS00703

£1,138.00

Specifications	TB114	TB214
Mounting	3 point	
Hitch cat.	1	
Weight (kg)	90	110
Height (mm)	600 (24')	
Working width (mm)	1200 (47')	1500 (59')
Depth (mm)	900 (35')	
Integrated rear blade	Std.	
Tipping lever	Manual	
Removable top hinged tail door	Std.	

Tipping transport box with rear blade, hinged tail door, and manual tipping lever.



Counterbalance Weights

Safer, more stable lifting and transport.

COUNTER BALANCE WEIGHTS

175kg W24TS00589
£711.00

225kg W24TS00052
£753.00

450kg W24TS00057
£909.00


800kg W24TS00552
£1,037.00

Model	Loader	Weight (kg)	Linkage category
BX	LA243	175	1
B1	LA213	175	1
B2	LA424	225	1
LX	LA545	225	1
L1-382	LA525	450	1
L1-452	LA805	450	1
L1-522	LA1055	450	1
L1-552	LA1055	450	1
L2-452	LA805	450	1
L2-522	LA1055	450	1
L2-622	LA1055	450	1

Add a counterweight to your Kubota tractor for safer, more stable lifting and transport.



Local Kubota Distributor



Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

<http://www.kubota.co.uk>

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

All prices are recommended retail prices in GBP as of March 2025, and are subject to value added tax. Subject to changes in price and product features. The general terms and conditions of KUBOTA UK apply. The publication of this price list renders all previous price lists invalid.

v_11/2025

